

# Aquavintage

## PRODUCT DESCRIPTION

Water based reactive stain, specially fit for ageing the wood in a simple and fast way. Only for interior use.



5L 1L

## TECHNICAL DATA

VISCOSITY	As water
SOLID CONTENTS	Depending on the colour
DENSITY	+/- 1,00 kg/l
GLOSS	-
THINNER	water
NMP FREE	
CONFORM EUROPEAN DECO-PAINT DIRECTIVE 2010	

## PREPARATION

Sand the wood with grain 100 – 120. Remove carefully sanding dust.

## USER TIPS

Before use stir and shake well. During processing, stir frequently. Apply plenty of Aquavintage with roller or brush. Then equalize the stain with a roller or brush. After drying, flatten the raised wood fibers with fine sanding paper when necessary.



## DRYING TIMES

Can be finished after 2 – 4 hours. Drying times are highly dependent on the environment temperature, the applied amount and the ventilation.



## APPLYING QUANTITY

7 - 12 m<sup>2</sup>/l depending on the type of wood and the wood sanding.

## AFTER TREATMENT

AQUAVINTAGE is a stain and gives no protection. Therefore it should be finished with Hardwaxoil or Wax from Ciranova. For varnish, please contact our technical service.

## PRODUCT INFORMATION

Storage life: 6 months in the original and well closed packaging. Not frost durable. Available in 8 colours.

## SPECIAL QUALITIES

Only use stainless material. After use, clean the material with water. This product should not be poured into drains.

**Stains should always be tested before the surface treatment. Used sanding grain, type of wood, ..... may affect the final colour.**

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

## Produced by Debal Coatings nv

Industrieweg 29 - 8800 Beveren-Roeselare  
Belgium  
tel. +32 (0) 51 30 11 40 fax +32 (0) 51 31 26 48  
ciranova@ciranova.be