


UN1CO



1l + 300ml

400ml + 120ml

VOC-FREE



- COMPLIES WITH THE STANDARD EN 717-1, CLASS E1
- NO VOC EMISSIONS DETECTED ACCORDING TO CDPH/EHLB/ STANDARD METHOD V1.1. 2010

Ciranova® products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However, they are drawn to our best knowledge and ability. The user must test the application of the product in the for him applicable conditions. Guarantee can not be derived out the text of this technical description.

PRODUCED BY DEBAL COATINGS NV

Industrieweg 29 – B 8800 Beveren-Roeselare
tel +32 (0) 51 30 11 40 fax +32 (0) 51 31 26 48
www.ciranova.be ciranova@ciranova.be

PRODUCT DESCRIPTION

UN1CO is a 2 component,1-coat oil from the newest generation using renewable natural raw materials. Thanks to its special technology there is only one coat needed to finish your parquet. The combination of the oil with the hardener results in a fast drying and excellent chemical and mechanical resistant finish. UN1CO is VOC and Cobalt free.

TECHNICAL DATA

VISCOSITY	+/- 40 SEC (DIN 4MM)
SOLID CONTENT	100% BY WEIGHT
DENSITY	+/- 0,95 KG/L
COBALT FREE	
VOC-FREE	
POT-LIFE	+/- 3 HOURS AFTER ADDING THE HARDENER
AVAILABLE IN 16 COLORS - SEE COLOR CATALOGUE	

PREPARATION

Sand the surface with grain 100-120 and remove afterwards the sanding dust.

TIP: for a more intense coloring of the wood, slightly wetten the floor first.

USER TIPS

Mix the oil with the hardener (100/30) and let the product rest for about 10 minutes. UN1CO can be applied with a buffing machine using a white or beige pad., by brush, cloth or sponge. Let the product dry for a few minutes. and remove the superfluous oil within 15 minutes with a white pad or cloth until the surface doesn't stick anymore. Check afterwards if the surface feels handdry.



DRYING TIMES

Slightly walkable after 24 hours drying depending on the type of wood, the temperature, the humidity.



APPLYING QUANTITY

+/- 50 - 60 m²/liter per coat

AFTER TREATMENT

Clean regularly with flooring soap Ciranova. Depending on the frequent use of the parquet, use maintenance oil periodically and for thorough cleaning, use Intensive Cleaner Ciranova.

ATTENTION : UN1CO needs +/- 2 weeks to fully cure. Don't use any water or maintenance products on the floor during this period.

PRODUCT INFORMATION

Shelf life : 1 year in original and un-opened original packaging.

Potlife : +/- 3 hours.

Storage frostfree.

SPECIAL QUALITIES

Dried and used cloths or pads should be plunged in water because of the danger for spontaneous combustion.