

# Wax remover



5L 1L

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

### Produced by Debal Coatings nv

Industrieweg 29 - 8800 Beveren-Roeselare

Belgium

tel. +32 (0) 51 30 11 40

fax +32 (0) 51 31 26 48

ciranova@ciranova.be

### PRODUCT DESCRIPTION

Cleans and removes old layers of wax polish.

### TECHNICAL DATA

APPEARANCE	uncoloured liquid
ODOUR	alcohol
DENSITY	0,73
VISCOSITY	8 sec/DIN 4 mm (20°C)

### USE

To remove old layers of wax.

### PREPARATION

You can use it immediately on the surface.

### USER TIPS

Put some wax remover on a cloth and wipe over the old wax layers. With several layers, you must repeat this action. After applying, the wood surface receives a flat outlook.



### DRYING TIMES

By room temperature: 30 minutes. After one hour you can wax again.



### APPLYING QUANTITY

It depends of the amount of layers you must remove. About 5 m<sup>2</sup>/l.

### AFTER TREATMENT

Afterwards you can wax again.

### PRODUCT INFORMATION

Shelf life: up to 2 year in closed packaging.

### SPECIAL QUALITIES

This product is a solvent, highly flammable, so read the label. All remainders are chemical waste.