

## MAINTENANCE OILED WOODEN FLOORS



### IN GENERAL

During the first 10 days, the Hardwaxoil hardens. Some precautionary actions are recommended.

- Don't cover the parquet or put a carpet.
- Don't move heavy furniture or chairs (hauling)
- Dust with a vacuum, broom or cloth (don't use impregnation substances)
- Apply adequate protection (felt) under the legs of tables and chairs.

### MAINTENANCE

An oiled floor can be vacuumed, be swiffered or treated with a dry mop. Never treat an oiled floor too wet. An oiled floor must be regularly fed.

### REGULAR MAINTENANCE

The protection of an oiled floor can be increased by regularly treaten the floor with flooring soap Ciranova. Mix 4-5 small caps of parquet soap in 10 liters of lukewarm water. Apply the soap with a floor cloth or mop that is not too wet and move in the direction of the wood grain. Wring out the dirty floor cloth or mop and rinse it in clear water. Dry after 1 hour at room temperature. Flooring soap contains only natural raw materials and nourish the wood.



### AFTER TREATMENT

If the oiled wooden floor becomes dull and dirty, and soap residue and dirt have been encrusted, it's better to rinse the floor with Intensive cleaner Ciranova. Afterwards you need to treat the parquet with Maintenance oil Ciranova or Oil Refresh Ciranova.

### LOCAL RENOVATION

On heavily damaged areas (wine stains, cigarette stains, impacts,...) a local renovation can be performed. That's one of the advantages of oiled treated floors. Sand the damaged area and then re-treat with Maintenance oil Ciranova (1 or 2 layers). Treat the entire surface with Maintenance oil Ciranova® for a perfect and smooth view.

### ENTIRE RENOVATION

For a heavily used or improperly maintained parquet you can sand the entire surface, dust, and then apply two coats Hardwaxoil Ciranova® with roller, brush or pad. Or you can treat the entire surface with Intensive cleaner Ciranova and then apply 1 coat Hardwaxoil Ciranova.

Ciranova® products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However, they are drawn to our best knowledge and ability. The user must test the application of the product in the for him applicable conditions. Guarantee can not be derived out the text of this technical description.

**Produced by Debal Coatings nv**

Industrieweg 29 – B 8800 Beveren-Roeselare  
tel. +32 (0) 51 30 11 40 fax +32 (0) 51 31 26 48  
www.ciranova.be ciranova@ciranova.be