

TECHNICAL DATA SHEET

Liquid flooring wax



5L 1L

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

Produced by Debal Coatings nv
Industrieweg 29 - 8800 Beveren-Roeselare
Belgium

tel. +32 (0) 51 30 11 40
fax +32 (0) 51 31 26 48
ciranova@ciranova.be

PRODUCT DESCRIPTION

Especially made for the maintenance of waxed floors because of its excellent water-repellency and anti-slip qualities. The wax feeds the floor and gives a brilliant, deep shine.

TECHNICAL DATA

APPEARANCE	liquid
ODOUR	turpentine smell
DENSITY	0,8
VASTE STOF	12%

USE

For the maintenance of waxed floors.

PREPARATION

It is better to remove the old wax coats with Ciranova® Wax Remover.

USER TIPS

Shake well before use. Apply a thin coat of Ciranova® Liquid Flooring Wax by cloth and spread so that the wax can penetrate into the wood. Let the wax dry for 2 hours and buff the floor with cloth or polishing machine.



DRYING TIMES

2 hours at room temperature.



APPLYING QUANTITY

+/- 10 m²/l

AFTER TREATMENT

After drying, polish well with a cloth or polishing machine until the wood gets a beautiful shine.

PRODUCT INFORMATION

Available colours: clear, yellow and brown. Storage: store in a well ventilated place for up to 2 years. Flammable.

SPECIAL QUALITIES

Ciranova® Liquid Flooring Wax is made from a mixture of natural and synthetic raw materials and pure turpentine oil.