

UNICARE X-MATT



Ciranova products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However, they are drawn to our best knowledge and ability. The user must test the application of the product in the for him applicable conditions. Guarantee cannot be derived out the text of this technical description.

PRODUCT DESCRIPTION

A waterborne environmental friendly protective refresher for all matt Ciranova surfaces + laminate & LVT.

TECHNICAL DATA

Odour	fresh detergent smell
Appearance	colourless
PH-Value	8
Viscosity	high liquid
Density	1,05 gr/cm ³ at 20 °C

USE

For all types of indoors varnished, sealed or lacquered floors. Prevents the floor from early abrasion. New varnished or lacquered floor : wait 14 days before applying Unicare X-MATT.

PREPARATION

Make the floor dust-free.

APPLICATION

Pour some Unicare X-MATT on the floor and spread it out with even movements on the surface with a clean cloth or mop in the direction of the woodgrain to avoid marks.

DRYING TIMES

1 hour at roomtemperature.
Completely chargeable after 24 hours.

APPLYING QUANTITY

80 m² / L

AFTER TREATMENT

For regular maintenance use Hard Floor Fresh Ciranova.

PRODUCTINFORMATION

Storage : 18 months in closed and original packaging.

SPECIAL QUALITIES

Keep out of the reach of children. Do not mix with other cleaning products. If swallowed, seek medical advice immediately and show this label.

Produced by Debal Coatings nv

Industrieweg 29 – B 8800 Beveren-
Roeselare tel. +32 (0) 51 30 11 40 fax +32
(0) 51 31 26 48 www.ciranova.be
ciranova@ciranova.be